

TECHNICAL SPECIFICATION

Motor	16 Pole Shaded pole, permanent magnet synchronous
Mains Supply	240V 50Hz
Drive	Belt
Speeds	33 $\frac{1}{3}$ rpm 45 rpm
Speed Change	Manual
Wow and Flutter	Less than 0.1% (WRMS)
Signal to noise Ratio	Better than 47dB
Turntable Platter	Solid die-cast alluminium
Platter weight	1.65 pounds (0.75 kilo)
Tone arm	S shaped low mass
Effective arm length	220 mm
Offset angle	22°
Bias compensator	gravity type
Maximum usable cartridge weight	10 gram
Pickup lead	fully screened type
Amplifier connection	5 pin DIN plug left channel pin 3 right channel pin 5 earth pin 2
Headshell	Detachable, slotted cartridge mounting holes
Size	444 mm x 356 mm x 125 mm
Weight	11 pounds (5 kilos)

ANCILLARY EQUIPMENT

Headshell

Spare headshells are available from Amstrad.

Amplifiers and Speakers

The TP12D is suitable for use with virtually any amplifier.

The Amstrad range of Amplifiers, Tuner-Amplifiers and Speakers are particularly recommended.

Made in England by
A.M.S. TRADING (AMSTRAD) LTD.
89 RIDLEY ROAD, DALSTON,
LONDON, E8 2NH
Telephone: 01-249 5237
Cables: Amselec London E.8
Telex: 264869

DEALER'S STAMP