

USER MANUAL FOR BATTERY INSTALLATION

L62BL



iPod Mini
Replacement Battery

Please observe standard anti-static precautions whilst working inside the iPod. Replacing the battery requires a reasonable level of technical ability and proficiency in the use of hand tools. Maplin Electronics can take no responsibility for any damage occurring to your iPod while installing this replacement battery. You do so entirely at your own risk.

Read these instructions carefully first so that you thoroughly understand the process before starting.

1



Start by using the tip of a flat head screwdriver to pry the white plastic cover from the top of the iPod. It is attached with a small amount of glue.

2



Once the cover is off, use the mini Phillips head screwdriver to remove the two screws indicated.

3




Using the flat head screwdriver again, prise the bottom white plastic cover from the bottom of the iPod. It is also attached with a small amount of glue.

4



Beneath this cover is a small metal retaining clip. This should be prised out using the flat head screwdriver in each of the four corners.

5




Locate the connector at the bottom edge and very gently pop it off with the tip of the screwdriver.

6



Pushing from the bottom, slide the circuit board carefully out from the top of the iPod case.

7



The old battery can now be removed by lifting it from the circuit board.

8



Unplug the battery connector and remove the old battery. Plug in the new battery and position it on the circuit board. Slide everything back into the iPod case. Reassemble the iPod by putting back the two screws and metal clip. The white plastic top and bottom covers should stick back to their original glue. Finished! The iPod is now ready to be charged. This should be for at least 3 hours and preferably overnight.